SNDT Women's University

1, Nathibai Thackersey Road, Mumbai 400 020

+91 22 2203 1879 +91 22 2201 8226 Phone:



श्रीमती ना. दा. ठाकरसी विद्यापीठ

१, नाथीबाई ठाकरसी मार्ग

मुंबई ४०० ०२०

Telegram: UNIWOMEN Website: sndt.ac.in

June 05th, 2025

Estate Section/2025-26/70

SUB:Quotation for Repairs and renovation work of ground floor a Guest house bldg. at S.N.D.T.W.U. Pune Campus.

Madam/Sir,

Sealed quotations are invited for Quotation for Quotation for Repairs and renovation work of ground floor a Guest house bldg, at S.N.D.T.W.U. Pune Campus. Interested authorized vendors are supposed to submit their quote along with their detail profile in the format given in "Annexure A" on their company letter head. Quotation should be submitted to the office of "The Registrar" at Churchgate campus on or before 13th June 2025 Contractor should submit their quotes in two envelopes enclosed in single envelope along with Technical bid envelope & financial bid envelope. Subject should be mentioned on each envelop.

Envelop may contains following documents in respective envelop:

A) Technical Bid

- Profile of the vendor i.
- Work Experience Certificate from the concerned the organization where ii. work has been executed.
- iii. **GST** Certificate
- iv. **PAN Copy**
- If GST is not applicable then declaration of the same. v.
- vi. If GST is applicable, then No Dues Certificate authorized by a Chartered Accountant

B) Financial Bid

- vii. Mentioning including all taxes
- viii. If required work is mentioned component wise then the amount is to be given component wise in the prescribed format.

Quotation should be submitted in closed envelop and on top write the subject. As mentioned in the notification.

The University reserves the right to reject any or all quotations without assigning any reasons thereof.

Regards,

rof. Vilas D. Nandavadekar

(Registrar)

Registrar SNDT Women's University Mumbai - 20.

(Offer should filled on letter head) Annexure A

To,

The Registrar, SNDT Women's University, Churchgate, Mumbai

SUB:Quotation for Repairs and renovation work of ground floor a Guest house bldg. at S.N.D.T.W.U. Pune Campus.

Respected Madam/Sir,

With reference to subject cited above we would like to furnish our quote with best rate

possible as below:

Sr. No.	Description of work	Qty.	Unit	Rate	Amount
1	Removing cement tiles, or marble or polished Shahabad floor or dado without bed concrete including stacking the materials as directed with all leads, lifts etc.complete.	204.00	Sqm		
2	Removing the existing cement plaster of any thickness without causing dust nulsance and stacking the debris upto a distance of 50 metres or spreading in the	224.00	Sqm		
	compound and cleaning the site etc.				
3	Removing brick bat coba cincluding stacking the spoils as directed with all leads, lifts etc. complete.	7.5	Cum		
4	Removing doors and windows with frames and stacking the materials as directed with all leads, liftsetc.complete.	16.00	Nos		
5	Providing waterproof plaster in W.C. and bath 20 mm thick for dado incement mortar 1:3 with neat finishing floating using waterproofing compound at the rate of 1 kilogram.per bag of cement of approved make and manufacturer and curing (and filling joints of Nahani trap and any outlet by properly) etc.complete.	224.00	Sqm		
6	Providing and laying cast in situ/Ready Mix cement concrete in M15 of trap/granite/quartzite/gnnnnneiss metal for foundation and bedding/stepsincludingsteel centering,formwork,laying/pumping,compacting,rough ening them if special finish is to be provided,finishing uneven and honeycombed surface and curing etc. Complete. The cement Mortar 1:3 plaster is considered for rendering uneven and honeycombed surface,only.Newly laid cdoncrete shall be covered by gunny bag,plastic tarpaulin etc. (Wooden centering Will not be allowed.), with fully automatic micro processor based OPLC with SCADA enabled reversible Drum Type mixer/concrete Batch mix plant (Pan	10.00	Cum		

i	mixer)etc.complete.With fine aggregate (Crushed sand VSI Grade)			
7	Providing water proof bedding for flooring of Bath and WC 25 mm thick in C.M. 1:3 including using approved water proofing compound in specified proportion as per manufacturers specifications for per bag of cement including levelling, curing and covering 10 years gurantee on court fee Stamp paper of Rs.500/-including ponding test etc.complete.	27.00	Sqm	
8	Providing and fixing 10 cm C.I. Nahani Trap including C.I. grating bend and place of C.I. pipe upto the outside face of the wall complete.	12.00	Nos	
9	Providing and laying in trenches 15 mm dal.CPVC pipe including necessary excavation, fittings. Refilling trenches etc. complete including removing existing pipe line if necessary and conveying and stacking the same to PWD chowky or as directed etc. complete.	54.00	Rm	
. 10	Providing and laying in trenches 25 mm dal.C.P.V.C. pipe including necessary excavation, fittings, Refilling trenches etc.complete. Inclluding removing existing pipe line if necessary and conveying and stacking the same in PWD chowky or as directed etc.complete.	78.00	Rm	
11	Providing and laying in position flooring of telephone black/Amba White/Cat bary brown/Ruby red/Ocean Brown granite stone of approved shade and size 18 mm to 20 mm thick on bedd 1:6 cement mortar incluing cement floats sriking joints, pointing in C.M. 1:3 curing and cleaning etc.complete.	15.00	Sqm	
12	Providing and laying matt finish ceramic timles mof having size 30 cmX30 cm confiring to I.S. 15622/2006 (Group D II-A) and 7 to 8 mm thick for flooring in required position laid on a bed of 1:4 cement mortar including cement float, filling joint with white/coour edment slurry cleaning curing etc. Complete.	24.00	Sqm	
13	Providing and laying ceramic tiles having size 30 cm.X45 cm confirming to corresponding I.S. for dado and skirting in required position with readymade adhensive mortar of approved quality on plaster of 1:2 cement mortar including joint filling with white/colour cement slurry cleaning curing etc.complete.	104.00	Sqm	
14	Providing and laying vitrified mirror/glossy finish tiles decorative type having size 590 mm to 605 mmX 590 mm to 605 mm of 8 to 10 mm thickness and confirfmifing to IS.15622-2006 (group Bla) of approved make, shae an pattern for flooring in required position laid on a bed of 1:4 cement mortar including neat cement float, filling joints, uring and clearing etc. omplete.	92.00	Sqm	
15	Lowering down the debris obtained from breaking and removing the cement/plaster/burnt brick masonry of the first floor by any means without causing dust nuisance and damage to structure, stacking the same as and where directed including cleaning the site complete.	56.00	Cum	

	Shifting the debris out of building premises including	T.C. 0.0	C	1	
16	loading and unloading and site cleaning etc.complete.	56.00	Cum		4
	Providing and fixing Europedadnd type dwhite glazed				
	earthware water closet pan with UPVC seat and Iid with				
	chromium plated brass hinges and rubber buffers				
	including UPVC and vent pipe up to the outside face of				
	wall 10 litre enamelled low level flushing cisern with				
	fittings pipe stop tap brackets for fixing cistern 32 mm	2.00	D.Y		
17	dia. UPVC flush pipe with fittings and clamps,20 mm	3.00	Nos		
	dia.UPVC overflow pipe mosquito proof couplingss G.I.				
	chain and pulley, with water jet and fitting including				
	cutting and making good to the walls and floors testing				Length are
	etc. Complete. (prior approval of sample and brand by	11111111			
	Ex.Engineer is necessary before				
	Providing and fixing coloured glazed earthenware wash				41. 3. 5
	hand basin of 45 cm X 30 cm size including cold water			3-1	1
	pillar tap/col and hot water pillar tap brackets,rubber	4.00	Nos	1. Ik	
18	plugs and brass chain, stop tap and necessary pipe	4.00	NUS		
	onnection including P.V.C. waste pipe and trap up to the				
	outside face of the wall. Making good the damaged	L WINE			
	surface, testing etc.complete.				
	Providing and fixing 32 mm thickmone piece single				
	mouled puff ABSTONE BUTADYNE STRINE (abs) Door			1 101	
	shutter for internal use including toiles made up of			1., .	
19	outer ABS sheet of 1:2 mm thick having puff insulation	7.00	Sqm		
19	of 35 to 40 kg/cum.density and 10 mm dia. For steel	'			
	bars 2 Nos., wooden block to receive fixtures, having				
	M.S. hinges 100 mm length, M.S. handles 150 mm length				
	and 10 mm dia sliding doors built etc.complete.				8
	Providing and fixing 1st class white glazed earthenware		pas a manufación in uma para mariar del discrettiro. Más cen		
	Orissa type W.C. Pan 580 mm dia including P or S trap				
	cast iron soil and Vent pipe upto the outside face of the				
20	wall (1:5:1 0) cement concrete bedding 15 mm thick,	1.00	Nos	8	
	1				
	time.				
	Net Total				
	10 liter P.V.C. flushing cistern with all necessary pipe conne ction etc.complete Total Taxes will be paid at actual at the prevailing time.				