

SNDT Women's University

1, Nathibai Thackersey Road,
Mumbai 400 020
Phone: +91 22 2203 1879
Fax: +91 22 2201 8226



श्रीमती ना. दा. ठाकरसी विद्यापीठ
१, नाथीबाई ठाकरसी मार्ग
मुंबई ४०० ०२०
Telegram: UNIWOMEN
Website: sndt.ac.in

Estate Section/2024-25/361

February 13th, 2025

SUB: Quotation for Refurbishment of GYM room 1 & 2 at 4th floor in Patkar Hall bldg. at S. N. D. T. Women's University, Churchgate Campus.

Madam/Sir,

Sealed quotations are invited for Quotation for Refurbishment of GYM room 1 & 2 at 4th floor in Patkar Hall bldg. at S. N. D. T. Women's University, Churchgate Campus. Interested authorized vendors are supposed to submit their quote along with their detail profile in the format given in "Annexure A" on their company letter head. Quotation should be submitted to the office of "The Registrar" at Churchgate campus on or before 21st February, 2024. Contractor should submit their quotes in **two envelopes** enclosed in single envelope along with Technical bid envelope & financial bid envelope. Subject should be mentioned on each envelop.
Envelop may contains following documents in respective envelop:

A) Technical Bid

- i. Profile of the vendor
- ii. Work Experience Certificate from the concerned the organization where work has been executed.
- iii. GST Certificate
- iv. PAN Copy
- v. If GST is not applicable then declaration of the same.
- vi. If GST is applicable, then No Dues Certificate authorized by a Chartered Accountant

B) Financial Bid

- vii. Mentioning including all taxes
- viii. If required work is mentioned component wise then the amount is to be given component wise in the prescribed format.

Quotation should be submitted in closed envelop and on top write the subject. As mentioned in the notification.

The University reserves the right to reject any or all quotations without assigning any reasons thereof.

Regards,

Prof. Vilas D. Nandavadekar

(Offer should filled on letter head)

Annexure A

To,

The Registrar,
SNDT Women's University,
Churchgate, Mumbai

Sub: Quotation for Refurbishment of GYM room 1 & 2 at 4th floor in Patkar Hall bldg. at S. N. D. T. Women's University, Churchgate Campus.

Respected Madam/Sir,

With reference to subject cited above we would like to furnish our quote with best rate possible as below:

Sr. No.	Description of work	Qty.	Unit	Rate	Amount
1	Removing the existing cement plaster of any thickness without causing dust nuisance and stacking the debris upto a distance of 50 metres or spreading in the compound and cleaning the site etc. complete.	122.36	Sqm		
2	Removing loose rust from the reinforcement bars by wire brushing, light hammering etc. and applying sulphate and chloride free inorganic single component rust remover Rusticide as approved by Engineer in charge conforming to IS 9077. The rusted surface shall become blackish non rusted colour. After 24 hours of application of rust remover, loose particles shall be removed by brush. Apply one more coat of Rusticide. Apply bonding coat slurry of high performance acrylic polymer - Methyl 2-methylpropenoate copolymer with another enoate as approved by Engineer in charge on entire surface. Mix 1 Kg of acrylic polymer with 0.5 Kg of cement. Finish it with ready to use repair polymer modified mortar based on special cements, aldehyde based polymers with thixotropy modifying agents as approved by Engineer in charge (The Polymer Modified Mortar (PMM) should attain min. compressive strength of 20 N/mm ² in 1 day and 30 N/mm ² in 7 days) by adding 13 - 16% water by weight of polymer	24.94	Sqm.		

	modified mortar for treatment to the damaged RCC members. Add 1 Kg of Migrating Corrosion Inhibiting Admixture as approved by Engineer in charge per 25 Kg bag of polymer modified mortar. After mixing polymer modified mortar, it can be trowel applied or sprayed. When applying by hand, polymer modified mortar must be forced tightly into the substrate to ensure complete contact with the substrate. (If scaffolding is required, same shall be provided and will be paid under relevant item) (Upto 15 mm thickness at a time).				
3	Providing internal cement plaster 6 mm thick in a single coat in cement mortar 1:4 without neeru finish to concrete surface in all positions including scaffolding and curing etc. complete.	52.70	Sqm		
4	Providing internal cement plaster 20mm thick in Single coats in cement mortar 1:5 without neeru finish, to concrete, brick surface, in all positions including scaffolding and curing etc. complete	69.66	Sqm		
5	Providing and applying one pack bonding coat between concrete members like RCC slabs, columns, beams, chajjas, pardis etc and cement mortar plaster using Hack Aid Plast of approved make & approved by Engineer in charge. Clean the concrete surface thoroughly to remove dust, dirt, grime, deshuttering oils and rub down to a clean surface. Apply Hack Aid Plast of approved make & approved by Engineer in charge by spray on the entire concrete surface. Provide a lean cement - sand dash coat over the same. Allow the dash coat to set for around 24 hours. Further plastering as per specifications can continue.	52.70	Sqm		
6	Providing and applying priming coat on concrete/ masonry/ Asbestos Cement plastered surfaces including scaffolding if necessary, preparing the surface by thoroughly cleaning oil, grease, dirt and other foreign matter and sand papering as required etc. complete.	227.16	Sqm		
7	Lowering down the debris obtained from breaking and removing the cement plaster / burnt brick masonry of the first floor by any means without causing dust nuisance and damage to structure, stacking the same as and where directed including cleaning the site complete.	8.17	Cum		

8	Removing and kind of debris including loading in truck and conveying to dumping point approved by MCGM , unloading , spreading etc. Complete with all leads and lifts.	8.170	Cum		
9	Providing and fixing 10mm thick special feature (Anti fatigue cushion) cushioned square shape (50cmx50cm) crum rubber PU bonded flooring for gym room with cleaning etc. Complete	92.00	Sqm		
10	Providing and fixing Mirrors of approved Indian quality, copper plated with 3/8" thick plywood backing in the masonry etc complete	46.56	Sqm		
11	Providing and supplying 12mm thick toughen glass main door with computer machine polish on all edges with floor spring and 4 handle complete with lock and other necessary hardware like pivot, bottom lock etc. complete as directed	5.67	Sqm		
12	Supplying Glass obscured (bajara) 5mm as per approved sample by the Engineer in charge with all lead and lifts etc. complete and stacking wherever directed.	13.33	Sqm		
13	Carpenter II class skilled	6.00	Day		
14	Mazdoor-Unskilled Heavy Male	6.00	Day		
15	Providing and fixing Air vent grill made of solid wood with painting & finishing etc. Complete.	19.66	Sqm		
16	Providing and fixing in position Anodized extruded aluminum partitions, with fully Aluminium composite panel Sheet having frame made out of extruded tubular section of size 63.5mm x 38.1 mm x 1.65mm thick. Aluminium composite panel fixed with aluminum glass clips and rubber cushioning beading to Aluminium composite panel sheets as per approved drawing etc.. complete	18.63	Sqm		
17	Providing and fixing laminate sheet covering on existing frame made up of 6mm thick marine plywood of a requisite manufacture ie. Anchor/Century/Kennwood / Duro/ Jet or equivalent generally conforming to IS 710-1980 finished with formica laminate sheet of approved colour and in pattern with antitermite treatment to plywood with necessary hardware etc. complete including all leads & lifts and as per drawing and instruction of engineer in charge	20.00	Sqm		
18	Providing and applying washable oil-bound distemper of approved colour and shade to old and new surfaces in two coats including scaffolding, preparing the surfaces. (excluding the primer coat.) etc. complete.	227.16	Sqm		

19	Providing and applying Two coats of wall care Putty on plastered surface and Ceiling and Walls to prepare surface even and smooth of approved make, etc complete.	227.16	Sqm		
	Total				
	Taxes will be paid at actual at the prevailing time.				
	Net Total				